



# ULTRATECH 10W30 SN/CF

Code: 1204

Date: 10-05-2015

## DESCRIPTION

**ULTRATECH 10W30 SN/CF** is for modern petrol and light diesel engines for cars and light trucks. It meets the latest API SN requirements and provides the highest protection against sludge, deposits, valve train wear and catalytic converter fouling.

## SUMMARY OF BENEFITS

- ULTRATECH 15W40 SN offers outstanding control of cam wear
- Better piston cleanliness and excellent engine sludge protection
- Excellent control of oxidation and oil loss due to volatility
- Better high temperature wear protection
- Fully compatible with prior ILSAC and API categories

## SPECIFICATIONS

- ACEA A3/ B4
- API SN/CF
- SAE 10W30
- CHRYSLER SERVICE FILL
- LEGACY GM SERVICE FILL

## TECHNICAL DATA

CHARACTERISTICS	ULTRATECH 10W30 SN/ CF
Specific gravity at 15 C	0.878
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	76.0
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	11.5
Viscosity index	145.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

**TRITECH LUBRICANTS AND SALES PTY LTD**  
151 Colemans Road, Dandenong South VIC 3175  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)  
Phone: 1300 46 33 33

