

DESCRIPTION

ULTRATECH 15W40 SN is the latest petrol oil designed for cars and light trucks, especially those with high revving engines and meets the latest SN requirements. Highlights of this oil include the highest protection against sludge, deposits, valve train wear and catalytic converter fouling due to phosphorous volatility.

SUMMARY OF BENEFITS

- **15W40 SN** offers outstanding control of cam wear
- Better piston cleanliness and excellent engine sludge protection
- Better high temperature wear protection
- Excellent control of oxidation and oil loss due to volatility

SPECIFICATIONS

- ACEA A3/B4
- API SN/CF
- FORD SERVICE FILL
- CHRYSLER SERVICE FILL
- LEGACY GM SERVICE FILL

TECHNICAL DATA

| CHARACTERISTICS | 15W40 SN/CF |
|--|-------------|
| Specific gravity at 15 C | 0.870 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 102.0 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 14.2 |
| Viscosity index | 142.0 |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C