



# 2 STROKE - TC SEMI SYNTHETIC

Code: 1900  
Date: 25-04-2016

## DESCRIPTION

**2-STROKE SEMI SYN** is a premium low ash, high performance semi synthetic two stroke engine oil for use in non-outboard applications. It provides the highest level of protection from piston and exhaust deposits, and exceptional anti-scuff protection.

## SUMMARY OF BENEFITS

**2-STROKE SEMI SYN** is suitable for all air cooled Two Stroke engines operating on leaded or unleaded petrol with or without injection lubrication systems:- motorcycles, lawnmowers, brushcutters, generators, pumps, agricultural machinery and chainsaws.

**2-STROKE SEMI SYN** should be used in conjunction with the engine manufacturers recommendation regarding fuel/oil ratio, however, in the absence of such information a 50 to 1 fuel/oil ratio is advised.

## SPECIFICATIONS

- JASO TC
- JASO FC
- ISO-L-EGC
- TISI 1040-2534

## TECHNICAL DATA

CHARACTERISTICS	TWO STROKE SEMI SYN
Color	Green
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	54.5
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	8.6
Viscosity index	133

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)

