

DESCRIPTION

ULTRATECH 15W40 CH-4 is a mid ash, heavy duty multigrade diesel engine oil designed for use in high speed, four stroke diesel engines meeting the requirements of American, European and Japanese engine manufacturers. **ULTRATECH 15W40 CH-4** has been formulated for heavy duty service in engines specifically designed for on- highway conditions as well as being suitable for a wide range of heavy-duty off-highway applications.

SUMMARY OF BENEFITS

- Sludge and soot control
- Superior friction and wear control

SPECIFICATIONS

- CUMMINS CES 20076, 20072, 20071
- ACEA E5/ E3
- API CH-4, CG-4/ CF-4, / SJ
- VOLVO VDS-3
- MTU / DDC TYPE 2
- CAT ECF-1
- MACK EO-M+
- MB 228.3
- JASO DH-1

TECHNICAL DATA

CHARACTERISTICS	ULTRATECH 15W40 CH-4
Specific gravity at 15 C	0.872
Kinematic viscosity at 40 C, mm ² /s (cSt)	101
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.0
Viscosity index	140

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

