



GLOBALTECH 15W40 CI-4/SL

Code: 2002

Date: 04-05-2018

DESCRIPTION

GLOBALTECH 15W40 CI4 is a low ash, superior performance multigrade engine oil designed for use in most four stroke diesel engines, including those fitted with emission and electronic control systems in order to meet the latest standards and in particular for long haul extended drain cycle operations.

SUMMARY OF BENEFITS

- Recommended for turbocharged high speed engines
- Excellent sludge and soot control
- Recommended for post 1994 engines
- Superior friction and wear control.

SPECIFICATIONS

- API CI-4, CH-4/SL, SJ
- ACEA E7, E5, E3, A2/B2
- ALLISON C4
- CAT ECF-2, ECF-1A
- MACK EO-M+, EO-M, EO-N
- MTU CATEGORY 1
- DETROIT DDC 93K215
- MB 228.3
- MAN M3275
- VOLVO VDS-3, VDS-2
- CUMMINS CES 20078, 20077, 20076
- IVECO T2 E5
- RENAULT RLD, RLD-2
- JASO DH-1

TECHNICAL DATA

| CHARACTERISTICS | GLOBALTECH 15W40 CI-4/SL |
|--|--------------------------|
| Specific gravity at 15 C | 0.8730 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 108 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 14.0 |
| Viscosity index | 142 |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: info@tritechlubricants.com

Web: www.tritechlubricants.com



AUSTRALIAN MADE AND
AUSTRALIAN OWNED