



GLOBALTECH 15W40 CI-4/SL

Code: 2002

Date: 12-04-2019

DESCRIPTION

GLOBALTECH 15W40 CI4 is a low ash, superior performance multigrade engine oil designed for use in most four stroke diesel engines, including those fitted with emission and electronic control systems in order to meet the latest standards and in particular long haul extended drain cycle operations.

SUMMARY OF BENEFITS

- Recommended for turbocharged high-speed engines
- Excellent sludge and soot control
- Recommended for post 1999 engines
- Superior friction and wear control.

SPECIFICATIONS

- API CI-4, CH-4/SL, SJ
- ACEA E7, E5, E3, A2/B2
- ALLISON C4
- CAT ECF-2, ECF-1A
- MACK EO-M+, EO-M, EO-N
- MTU CATEGORY 1
- DETROIT DDC 93K215
- MB 228.3
- MAN M3275
- VOLVO VDS-3, VDS-2
- CUMMINS CES 20078, 20077, 20076
- IVECO T2 E5
- RENAULT RLD, RLD-2
- JASO DH-1

TECHNICAL DATA

CHARACTERISTICS	GLOBALTECH 15W40 CI-4/SL
Specific gravity at 15 C	0.8730
Kinematic viscosity at 40 C, mm ² /s (cSt)	110
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.5
Viscosity index	135

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

