

DESCRIPTION

ATF UNIVERSAL is the latest generation in automatic transmission fluid technology, and has been developed to cover a wide range of specific vehicle applications. **ATF UNIVERSAL** utilizes premium highly stable mineral base oil and new generation automatic transmission fluid additive technology to improve transmission durability, shift performance and minimize transmission shudder. It provides excellent oxidation and thermal stability resulting in superior wear protection.

SUMMARY OF BENEFITS

- Anti shudder durability for smooth shifting performance
- Enhanced wear protection

SPECIFICATIONS

- HONDA Z1
- ALLISON C-4
- ZF TE-ML-14A
- VOLVO 97341
- BTR 5M-52 (FORD 95LE)
- VOITH H55.6335.XX
- MAN 339 TYPE V-1, Z-1
- MITSUBISHI SP-II AND SP-III
- MB, VW AND BMW 4 AND 5 SPEED AUTOMATICS
- GM DEXRON®
- JASO 1-A
- TOYOTA T-III, T-IV
- FORD MERCON V
- NISSAN MATIC D & J
- CATERPILLAR TO-2
- Many other common ATF's

TECHNICAL DATA

CHARACTERISTICS	UNIVERSAL
Specific gravity at 15 C	0.8673
Kinematic viscosity at 40 C, mm ² /s (cSt)	41.30
Kinematic viscosity at 100 C, mm ² /s (cSt)	8.0
Viscosity index	170.0
Colour	RED

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C