



# GEAR LUBE S/SYN

## 75W80 GL-4

Code: 4002

Date: 20-04-2016

### DESCRIPTION

**75W80 GL-4 Semi Synthetic** is a high viscosity index, semi synthetic manual gearbox lubricant containing sophisticated extreme pressure additives and base oils. It is designed to give maximum protection to transaxles and gearboxes operating under the most arduous conditions.

### SUMMARY OF BENEFITS

- Smooth shift
- Enhanced oxidation stability
- Semi Synthetic for longer life
- Superior wear protection

### SPECIFICATIONS

- CHRYSLER MS 9224
- API GL-4
- MB 235.10
- LAND ROVER MTF 94
- ZF TE-ML 02D
- HONDA MTF 7289

### TECHNICAL DATA

CHARACTERISTICS	GEAR OIL 75W80 GL-4 SEMI SYN
Specific gravity at 15 C	0.865
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	55.0
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	9.80
Viscosity index	165

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

#### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)

