



LIMITED SLIP GEAR LUBE LS90 GL-5

Code: 4006

Date: 15-08-2016

DESCRIPTION

LS 90 GL-5 GEAR OIL Is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers.

SUMMARY OF BENEFITS

- **LS 90 GL-5 GEAR OIL** Should be used in all limited slip differentials including Ford "Traction - Lok" Type.

SPECIFICATIONS

- MILITARY SPECIFICATIONS MIL-PRF-2105E
- ZF TE-ML 07A, ZF TE-ML 08
- FORD- M2C118-A
- DAIMLER MS5630
- DANA 40819
- ISO 12925-1 CKC/CKD
- DIN 51517 PART 3
- AGMA 9005-E02
- API GL5
- USS 224

TECHNICAL DATA

CHARACTERISTICS	GEAR OIL LS90 GL-5
Specific gravity at 15 C	0.890
Kinematic viscosity at 40 C, mm ² /s (cSt)	170
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.0
Viscosity index	110

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

