



GEAR LUBE LS140 GL-5

Code: 4009

Date: 10-05-2016

DESCRIPTION

GEAR LUBE LS 140 GL-5 is a thick extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid differentials both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers to reduce squeal and protect against heavy and shock loads.

SUMMARY OF BENEFITS

- Protects differentials, final drives and axles from heavy loads and shock loading
- High temperature stability and oxidation resistance
- Offers superior wear protection, prevents squeals and provides smooth take off.
- Recommended for heavy duty applications like 4WDs, trucks, trailers, farm machinery, construction equipment and other heavy applications.

SPECIFICATIONS

- API GL-5
- MT-1
- CHRYSLER MS-9020
- US STEEL224:
- 51517 PART III:
- MIL-L-2105E

TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE LS140 GL-5
Specific gravity at 15 C	0.911
Kinematic viscosity at 40 C, mm ² /s (cSt)	330
Kinematic viscosity at 100 C, mm ² /s (cSt)	26.0
Viscosity index	103

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
 151 Colemans Road, Dandenong South VIC 3175
 Web: www.tritechlubricants.com
 Phone: 1300 46 33 33

