



LIMITED SLIP GEAR LUBE LS-140

Code: 4009
Date: 10-05-2016

DESCRIPTION

Extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers.

SUMMARY OF BENEFITS

Should be used in all limited slip differentials including Ford "Traction - Lok" type.

SPECIFICATIONS

- MIL-PRF-2105E
- MACK GO-J
- SAE J2360
- NISSAN 4WD
- MT-1
- GL-5

TECHNICAL DATA

CHARACTERISTICS	LS 140
Specific gravity at 15 C	0.911
Kinematic viscosity at 40 C, mm ² /s (cSt)	330.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	26.0
Viscosity index	103

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

