



# SUPER HYDRAULIC HVI ISO: 46

Code: 5103

Date: 03-10-2019

## DESCRIPTION

**SUPER HYDRAULIC HVI 46** is a premium performance anti-wear hydraulic oil, made with high quality base oils and very shear stable viscosity index improvers. It is designed to maintain close viscosity control over wide temperature range applications. Outstanding cold flow characteristics in low temperature conditions and excellent film strength in high pressure, high temperature conditions.

## SUMMARY OF BENEFITS

- Excellent oxidation stability, good deposit control
- Resistance to aging and corrosion
- Wide-temperature operating range
- Offers good demulsifying properties
- Excellent filterability
- Outstanding wear and corrosion protection

## SPECIFICATIONS

- DENISON TP02100
- VICKERS 1-286-S
- DIN 51524 Part 3 (HVLP)
- US STEEL 126 & 127
- AFNOR NF E 48-603 HM and HL

## TECHNICAL DATA

CHARACTERISTICS	SUPER HYDRAULIC HVI 46
Specific gravity at 15 C	0.852
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	46
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	8.2
Viscosity index	150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)

Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)



AUSTRALIAN MADE AND  
AUSTRALIAN OWNED