



BRAKE & CLUTCH FLUID - DOT 4

Code: 6010

Date: 25-08-2015

DESCRIPTION

DOT 4 BRAKE FLUID is a high performance polyglycol brake fluid designed for use in a wide range of brake and clutch applications where DOT 4 specifications are called for.

DOT 4 BRAKE FLUID has a high boiling point and low volatility and is recommended for re-fill or top-up of brake and clutch systems in passenger cars, light and heavy commercial vehicles, four wheel drives, tractors and motorcycles.

SUMMARY OF BENEFITS

DOT 4 BRAKE FLUID can be used for disc or drum brake and clutch systems and is developed to meet Australian and International standards.

SPECIFICATIONS

- ISO 4925
- SAE J1703
- GMH HN 1796
- FORD ESW FM6C-2
- US FMVSS 116 DOT 3 AND DOT 4
- AUST. STAND. 1960-1983 GRADE 3

TECHNICAL DATA

CHARACTERISTICS	BRAKE FLUID DOT 4
BOILING POINT DEG. C (MIN DRY)	280
BOILING POINT DEG. C (MIN WET)	180

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

