

DESCRIPTION

COMPRESSOR OIL 68 is an air compressor lubricant formulated from highly refined base oils and state of the art non-hydrolyzing anti wear additives developed for rotary screw and smaller reciprocating compressors. The result is a finished product which has long life, protects compressor components from wear and which also separates readily from water. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C. Drain intervals can be extended to up to 4000 hours in rotary screw compressors where an oil test program is in place.

SUMMARY OF BENEFITS

- Long drain intervals
- Anti wear additives
- Robust rust and oxidation inhibitors
- Ash-free formulation

SPECIFICATIONS

- ISO / DP 6521 DAA, DAB, DAH, DAG
- DIN 51506 VBL, VCL, VDL

TECHNICAL DATA

CHARACTERISTICS	COMPRESSOR 68
Specific gravity at 15 C	0.8650
Kinematic viscosity at 40 C, mm ² /s (cSt)	68.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	9.1
Viscosity index	110.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
 Phone: 1300 46 33 33, Email: info@tritechlubricants.com
 Web: www.tritechlubricants.com

