

COMPRESSOR OIL

ISO: 68

Code: 7012
Date: 15-08-2016

DESCRIPTION

COMPRESSOR 68 is an air compressor lubricant formulated from highly refined base oils and state of the art non-hydrolyzing anti wear additives developed for rotary screw and reciprocating air compressors. The result is a finished product which has long life, protects compressor components from wear and also separates readily from water. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C. Drain intervals can be extended to up to 4000 hours in rotary screw compressors where an oil test program is in place.

SUMMARY OF BENEFITS

- Long drain intervals
- Anti wear additives
- Rust and oxidation inhibitors

SPECIFICATIONS

- DIN 51527 PART 2
- AFNOR NF E 48-603
- GE GEK 32568 A/C
- CEGB 207001
- MIL-L-17672 D
- US STEEL 120
- DIN 51524, PART 1, 2 AND 3(HLP, HLVP)
- DIN 51515 PART 1 AND PART 2
- CINCINATTI P38, P55, P57, P62
- MITSUBISHI HEAVY INDUSTRIES E00-87182
- DP 6521 (DAA,DAB,DAH,DAG)
- DIN 51506(VBL, VCL, VDL)
- DENISON HFO
- BB HTGD 90117
- VDMA 24568
- TLV 9013
- BS 489

TECHNICAL DATA

CHARACTERISTICS	COMPRESSOR 68
Specific gravity at 15 C	0.8660
Kinematic viscosity at 40 C, mm ² /s (cSt)	68.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	9.10
Viscosity index	110.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

