

## DESCRIPTION

**COMPRESSOR 100** is an air compressor lubricant formulated from highly refined base oils and state of the art non-hydrolyzing anti wear additives developed for reciprocating air compressors. The result is a finished product which has long life, protects compressor components from wear and also separates readily from water. They are designed for use of up to 2000 hours with air discharge temperatures of up to 85°C.

## SUMMARY OF BENEFITS

- Long drain intervals
- Anti wear additives for wear protection
- Robust rust and oxidation inhibitors
- Ash-free formulation

## SPECIFICATIONS

- ISO / DP 6521 DAA, DAB
- DIN 51506 VBL, VCL, VDL

## TECHNICAL DATA

CHARACTERISTICS	COMPRESSOR 100
Specific gravity at 15 C	0.870
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	100.0
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	12.0
Viscosity index	110.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
**Phone:** 1300 46 33 33, **Email:** [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
**Web:** [www.tritechlubricants.com](http://www.tritechlubricants.com)

