



CHAIN AND BAR ISO: 150

Code: 7031

Date: 10-07-2018

DESCRIPTION

CHAIN AND BAR 150 is a tacky lubricant formulated for the protection of chains, bars and sprockets on chainsaws.

It is suitable for use with both automatic and manual operated oil systems and can be used on other chain driven equipment including motorcycles, lawnmowers and farm equipment.

SUMMARY OF BENEFITS

CHAIN AND BAR 150 will penetrate the links of chains providing thorough lubrication. It is blended with anti-wear additives that give increased working life to the bar, sprockets and chain. The tacky quality of the oil will resist excessive throw off and form a strong protective film at rest. CHAIN AND BAR 150 will assist to keep the saw clean by flushing dust, gum and wood chips away, remove pitch and prevent further pitch build-up on the chain and bar.

SPECIFICATIONS

- ISO: 150

TECHNICAL DATA

CHARACTERISTICS	CHAIN & BAR 150
Specific gravity at 15 C	0.8660
Kinematic viscosity at 40 C, mm ² /s (cSt)	150.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	21.0
Viscosity index	161.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

