



# MOLYLITH BLACK GREASE EP2

Code: 8130

Date: 03-05-20158

## DESCRIPTION

**MOLYLITH BLACK GREASE EP2** is a lubricating grease formulated to meet the extreme conditions encountered on off- highway construction equipment as well as heavy duty applications. This product is a Lithium Complex thickened grease blended with high viscosity base fluids for exceptional film strength and is fortified with 3% molybdenum disulphide for additional load carrying capacity and anti-wear performance.

## SUMMARY OF BENEFITS

MOLYLITH BLACK GREASE EP2 is ideal for wet environments and better performance at high temperatures. Because it is lithium complex thickened grease, MOLYLITH BLACK GREASE EP2 has a high dropping point which also provides excellent protection in high temperature environments. Ideally suited for Truck and Farm applications.

## SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM COMPLEX
TEXTURE	TACKY
COLOUR	GREY/BLACK
DROPPING POINT °C	250 MIN
FOUR BALL WELD LOAD, KGS	500
BASE OIL VISCOSITY @40°C	460
OPERATING TEMPERATURE RANGE °C	-20 to 150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
 Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
 Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)



AUSTRALIAN MADE AND  
AUSTRALIAN OWNED