



SYNERGY 5W40 SN/CF

Code: 9160
Date: 10-05-2016

DESCRIPTION

SYNERGY 5W40 is a full synthetic petrol/diesel motor oil formulated with advanced synthetic base stocks, premium additive and a broad viscosity rating providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals.

SYNERGY 5W40 is a multi viscosity, low pour point motor oil ensuring quick lubrication to all moving parts during cold weather starts. It also provides protection against wear and corrosion, prevents oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits.

SUMMARY OF BENEFITS

SYNERGY 5W40 meets or exceeds the requirements of an SN/CF engine oil and is suitable for unleaded or leaded fuelled engines, diesel powered cars, turbo charged and naturally aspirated engines and LPG engines

SYNERGY 5W40 is a low ash formulation designed to maintain outstanding engine cleanliness

SPECIFICATIONS

- API SN (ENERGY CONSERVING)
- VW 501.01, 505.00
- ACEA A3/B4
- MB –APPROVAL 229.3
- PORSCHE
- BMW

TECHNICAL DATA

CHARACTERISTICS	SYNERGY 5W40 SN/CF
Specific gravity at 15 C	0.860
Kinematic viscosity at 40 C, mm ² /s (cSt)	99.5
Kinematic viscosity at 100 C, mm ² /s (cSt)	15.0
Viscosity index	165

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

