



SYNERGY EURO SYN 10W40 E4/E6 LOW SAPS

Code: 9233

Date: 10-07-2016

DESCRIPTION

SYNERGY EURO E4/E6 is a fully synthetic, ultra high performance heavy duty diesel engine oil. It meets and complies with the demanding requirements of Euro 5 exhaust emission legislation. **SYNERGY EURO E4/E6** is ideally designed for European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3, Euro 4 and Euro 5 exhaust emission legislation.

SUMMARY OF BENEFITS

- Full synthetic formulation
- Suitable for use where particulate filters are used
- Outstanding low temperature viscometrics for reduced wear at start up
- Low SAPS (Sulfated Ash, Phosphorous and Sulfur)
- Super extended drain intervals surpassing any mineral or American diesel type lubricant
- Reduces fuel consumption due to superior technology
- Excellent soot and sludge control resulting in cleaner engines

SPECIFICATIONS

- API CI-4
- MAN 3477/3271-1
- MB 228.51 / MB 226.9
- ACEA E4-08 / E6-12 / E7-12
- RENAULT TRUCK RLD/RLD-2
- MACK EO-N
- MTU TYPE 3.1
- VOLVO VDS 3
- CUMMINS CES 20076 / CES 20077
- DEUTZ DQC III-10 LA
- DAF
- JASO DH-2
- SCANIA LDF-2 /LDF-3

TECHNICAL DATA

CHARACTERISTICS	10W40 E4/E6 LOW SAPS
Specific gravity at 15 C	0.8553
Kinematic viscosity at 40 C, mm ² /s (cSt)	94.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.5
Viscosity index	160.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

