



SYNERGY EURO 5W30 C3

Code: 9281

Date: 22-12-2020

DESCRIPTION

SYNERGY EURO 5W30 C3 is designed for European and Asian engines requiring SHPD (Super High Performance Diesel) level of performance and those which comply with the latest Euro emissions legislation. SYNERGY EURO 5W30 C3 is a full synthetic formulation and is suitable for use where particulate filters are used.

SUMMARY OF BENEFITS

- SYNERGY EURO 5W30 C3 has outstanding low temperature viscosity characteristics for reduced wear at start up and is a Mid SAPS European formulation but is also suitable for petrol engines requiring API SN performance.
- SYNERGY EURO 5W30 C3 has excellent soot and sludge control resulting in cleaner engines. Its ACEA C3/C2 rating offers excellent wear protection coupled with fuel economy benefits.

SPECIFICATIONS

Specifications below meet or exceed requirements and/or carry a written OEM approval where nominated *Suitable for use (For Outside of Warranty Period)*

- | | |
|--|--|
| <ul style="list-style-type: none"> • ACEA C2, C3 • API SN/CF • GM dexos 2 (OEM APPROVED) • BMW LONGLIFE 04 • MB 229.31 • MB 229.51 • MB 229.52 | <ul style="list-style-type: none"> • ACEA A5/B5 • PSA B71 2290 |
|--|--|

TECHNICAL DATA

CHARACTERISTICS	5W30 C3
Specific gravity at 15 C	0.852
Kinematic viscosity at 40 C, mm ² /s (cSt)	71.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	11.9
Viscosity index	165

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
 151 Colemans Road, Dandenong South VIC 3175
 Web: www.tritechlubricants.com
 Phone: 1300 46 33 33

