

DESCRIPTION

SYNERGY EURO 5W30 C3 is designed for European and Asian engines requiring SHPD (Super High Performance Diesel) level of performance and those which comply with the latest Euro emissions legislation. SYNERGY EURO 5W30 C3 is a full synthetic formulation and is suitable for use where particulate filters are used.

SUMMARY OF BENEFITS

- SYNERGY EURO 5W30 C3 has outstanding low temperature viscosity characteristics for reduced wear at start up and is a Mid SAPS European formulation but is also suitable for petrol engines requiring API SN performance.
- SYNERGY EURO 5W30 C3 has excellent soot and sludge control resulting in cleaner engines. Its ACEA C3/C2 rating offers excellent wear protection couples with fuel economy benefits.

SPECIFICATIONS

- ACEA A1/B1, A5/B5-12
- ACEA C2 -16, C3-16
- ILSAC GF-5
- VW 502.00, 505.00, 505.01, TL 52167
- API SN
- PSA GROUP B71 2290
- MB 229.31/ 229.51/ 229.52
- RENAULT RN0700 / 0710
- BMW LONGLIFE- 04
- GM DEXOS 2 (**OEM APPROVED**)
- LAND ROVER ST JLR 03.5004
- PORSCHE A40
- FORD WSS-M2C948-A / B
- FORD M2C917-A
- FORD M2C913-D (*Outside Warranty*)
- LAND ROVER ST JLR.03.5004
- VOLVO CAR VCCRBSO-2AE

TECHNICAL DATA

CHARACTERISTICS	5W30 C3
Specific gravity at 15 C	0.852
Kinematic viscosity at 40 C, mm ² /s (cSt)	69.8
Kinematic viscosity at 100 C, mm ² /s (cSt)	11.5
Viscosity index	159

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C