

DESCRIPTION

SYNERGY EURO 5W40 C3 is designed for European engines requiring SHPD (Super High Performance Diesel) level of performance and those which comply with Euro 1, Euro 2, Euro 3 and Euro 4 exhaust emission legislation. **SYNERGY EURO 5W40 C3** is a full synthetic formulation and is suitable for use where particulate filters are used.

SUMMARY OF BENEFITS

SYNERGY EURO 5W40 C3 has outstanding low temperature viscometrics for reduced wear at start up and is a dedicated European formulation with Low/ Mid SAPS (Sulfated Ash, Phosphorus and Sulfur)

SYNERGY EURO 5W40 C3 has excellent soot and sludge control resulting in cleaner engines and reduces fuel consumption due to superior technology

SPECIFICATIONS

- ACEA A3/B3-08, A3/B4-04
- VW 502 00/505 00/505 01
- ACEA C3-10, C2-08
- API SN/CF
- ACEA A1/B1 A5/B5
- MB –APPROVAL 229.31/ 229.51
- RENAULT RN0700 / 0710
- BMW LONGLIFE- 04
- GM DEXOS 2
- FORD WSS-M2C917-A
- PORSCHE A40

TECHNICAL DATA

CHARACTERISTICS	5W40 C3 LOW SAPS
Specific gravity at 15 C	0.853
Kinematic viscosity at 40 C, mm ² /s (cSt)	81.5
Kinematic viscosity at 100 C, mm ² /s (cSt)	13.45
Viscosity index	168

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

