



LIMITED SLIP SYNGEAR LS 75W90 GL5

Code: 9410

Date: 19-03-2018

DESCRIPTION

SYNGEAR LS 75W90 GL5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and low excellent low temperature characteristics due to its blend of selected synthetic base and extreme pressure additives. It is formulated to be suitable in limited slip differentials.

SUMMARY OF BENEFITS

SYNGEAR LS 75W90 GL5 is ideal for use in transaxles with combined manual gearbox, hypoid differentials and limited slip differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe of conditions.

SPECIFICATIONS

- MILITARY SPECIFICATIONS MIL-PRF-2105E
- ZF TE-ML 07A, ZF TE-ML 08
- FORD- M2C118-A
- DAIMLER MS5630
- DANA 40819
- ISO 12925-1 CKC/CKD
- DIN 51517 PART 3
- AGMA 9005-E02
- API GL5, MT-1
- USS 224

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR LS 75W90 GL5
Specific gravity at 15 C	0.857
Kinematic viscosity at 40 C, mm ² /s (cSt)	110
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.8
Viscosity index	179

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS

15 Leah Grove, Carrum Downs, Victoria, Australia 3201

Phone: +61 3 9708 2317, Fax: +61 3 9708 2318

Email: sales@tritechlubricants.com,

Web: www.tritechlubricants.com,



AUSTRALIAN MADE AND
AUSTRALIAN OWNED