

DESCRIPTION

POWERTRANS FLUIDS are high performance, multifunctional transmission/final drive fluids blended from premium base oils and selected additives designed to meet the requirements of Allison, Caterpillar and Komatsu final drives, powershift transmissions, torque converters, hydraulic systems, off-highway equipment and any other system calling for TO-4 specification.

SUMMARY OF BENEFITS

- Superior wear protection and load carrying capacity
- Improved power transfer efficiency
- Excellent friction performance
- Excellent thermal stability
- Outstanding yellow metal protection

SPECIFICATIONS

- API GL-4
- ALLISON C-4
- EATON FULLER
- DANA
- CATERPILLAR TO-4M
- CATERPILLAR TO-4
- CATERPILLAR TO-2
- EUCLID
- KOMATSU KES 07.868.1
- VICKERS M-2950-S

TECHNICAL DATA

CHARACTERISTICS	POWERTRANS 50
Specific gravity at 15 C	0.911
Kinematic viscosity at 40 C, mm ² /s (cSt)	317
Kinematic viscosity at 100 C, mm ² /s (cSt)	24
Viscosity index	96

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

