



HYDRAULIC OIL

ISO: 15

Code: 5000

Date: 21-01-2017

DESCRIPTION

HYDRAULIC OIL 15 is a premium hydraulic oil, containing high quality zinc antiwear additives.

HYDRAULIC OIL 15 promotes superior performance in oxidation protection, water tolerance, thermal stability and pump durability.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MACHINE P-68, P-69, P-70
- EATON BROCHURE 694 for 35VQ25A
- DIN 51524 Part 2 (HLP)
- GM LS2
- ISO 11158 Categories HM and HV
- ASTM D 6158 Type HM and HV
- AFNOR NF E 48-603 HM and HV

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 15
Specific gravity at 15 C	0.839
Kinematic viscosity at 40 C, mm ² /s (cSt)	15.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	3.48
Viscosity index	110

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
 Phone: 1300 46 33 33, Email: info@tritechlubricants.com
 Web: www.tritechlubricants.com

