



HYDRAULIC OIL ISO: 15

Code: 5000
Date: 21-01-2018

DESCRIPTION

HYDRAULIC OIL 15 is a premium hydraulic oil containing high quality anti-wear additives. HYDRAULIC OIL 15 promotes superior performance in oxidation protection, water tolerance, thermal stability and pump durability. It is also suitable for high-speed bearing and spindle lubrication.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties
- Excellent wear protection

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MACHINE P-68, P-69, P-70
- EATON BROCHURE 694 for 35VQ25A
- DIN 51524 Part 2 (HLP)
- GM LS2
- ISO 11158 Categories HM and HV
- ASTM D 6158 Type HM and HV
- AFNOR NF E 48-603 HM and HV

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 15
Specific gravity at 15 C	0.839
Kinematic viscosity at 40 C, mm ² /s (cSt)	15.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	3.62
Viscosity index	125

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

