

DESCRIPTION

HYDRAULIC OIL 22 is a premium hydraulic oil containing high quality anti-wear additives. HYDRAULIC OIL 22 promotes superior performance in oxidation protection, water tolerance, thermal stability and pump durability.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties
- Excellent wear protection

SPECIFICATIONS

- DENISON HF-0, HF-1 and HF 2
- CINCINNATI MACHINE P-68, P-69, P-70
- EATON BROCHURE 694 for 35VQ25A
- DIN 51524 Part 2 (HLP)
- GM LS2
- ISO 11158 Categories HM and HV
- ASTM D 6158 Type HM and HV
- AFNOR NF E 48-603 HM and HV

TECHNICAL DATA

CHARACTERISTICS	HYDRAULIC OIL ISO: 22
Specific gravity at 15 C	0.850
Kinematic viscosity at 40 C, mm ² /s (cSt)	22
Kinematic viscosity at 100 C, mm ² /s (cSt)	4.6
Viscosity index	126

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C