



SUPER HYDRAULIC HVI ISO: 32

Code: 5102

Date: 25-08-2018

DESCRIPTION

SUPER HYDRAULIC HVI 32 is a premium performance anti-wear hydraulic oil, made with high viscosity index improvers designed to maintain close viscosity control over wide temperature range applications.

SUMMARY OF BENEFITS

- Excellent oxidation stability
- Resistance to aging and corrosion
- Offers good demulsifying properties

SPECIFICATIONS

- DENISON TP02100
- VICKERS 1-286-S
- DIN 51524 Part 3 (HVLP)
- US STEEL 126 & 127
- AFNOR NF E 48-603 HM and HL

TECHNICAL DATA

CHARACTERISTICS	SUPER HYDRAULIC HVI 32
Specific gravity at 15 C	0.870
Kinematic viscosity at 40 C, mm ² /s (cSt)	32
Kinematic viscosity at 100 C, mm ² /s (cSt)	6.4
Viscosity index	150

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

