



INDUSTRIAL GEAR OIL

ISO: 1000

Code: 7027

Date: 10-04-2020

DESCRIPTION

IGO 1000 is a premium quality, heavy duty, high viscosity, extreme pressure industrial gear lubricant manufactured from highly refined base stocks and extreme pressure additives. Designed for use in heavily loaded industrial gear boxes and can also be used in slow moving heavily loaded sprockets, chain drives and slide guides.

SUMMARY OF BENEFITS

- Wear protection even on occasional metal to metal contact
- Protects against rust and corrosion
- Provides excellent micro-pitting protection
- Good oxidation and thermal stability for long life
- Excellent demulsibility for easy water separation

SPECIFICATIONS

- DAVID BROWN TYPES M, A, E
- AGMA 9005-E02
- DIN 51517 (PART 3)
- ISO 12925-1 CKD
- US STEEL 224

TECHNICAL DATA

CHARACTERISTICS	IGO 1000
Specific gravity at 15 C	0.910
Kinematic viscosity at 40 C, mm ² /s (cSt)	960
Kinematic viscosity at 100 C, mm ² /s (cSt)	49.0
Viscosity index	96.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

