



INDUSTRIAL GEAR OIL

ISO: 1000

Code: 7027

Date: 10-05-2015

DESCRIPTION

IGO 1000 is a premium quality, heavy duty industrial gear lubricant manufactured from highly refined base stocks and extreme pressure additives. Designed for use in all types of industrial gear boxes and can also be used in sprockets, chain drives and slide guides.

SUMMARY OF BENEFITS

- Excellent demulsibility
- Protects against rust and corrosion
- Good oxidation and thermal stability for long life
- Particularly suited for steel on bronze industrial worm gears.

SPECIFICATIONS

- DAVID BROWN S1.53.101E
- AGMA 250.04, 9005-D94
- DIN 51 517 (PART 3)
- U.S STEEL 224
- API GL-3

TECHNICAL DATA

| CHARACTERISTICS | IGO 1000 |
|--|----------|
| Specific gravity at 15 C | 0.915 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 1000 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 50.0 |
| Viscosity index | 95.0 |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

