



SYNERGY 5W50 SN/CF

Code: 9151

Date: 10-05-2015

DESCRIPTION

SYNERGY 5W50 is a full synthetic petrol/diesel motor oil formulated with synthetic base stocks, premium additive and a shear stable viscosity modifier providing the highest level of protection in the most demanding of conditions and allowing for maximum drain intervals.

SYNERGY 5W50 has excellent low temperature flowability ensuring quick lubrication to all moving parts during cold weather starts. It's high viscosity at operating temperature provides protection against wear during hard driving. It also protects against corrosion and its formulation prevents oxidative thickening and inhibits promotion of engine acids, sludge and varnish deposits.

SUMMARY OF BENEFITS

SYNERGY 5W50 offers excellent cold start flow for wear protection when it matters most. It has excellent oxidation and thermal resistance and its superior additives will keep the engine clean and free from sludge.

SPECIFICATIONS

- API SN
- VW 501.01, 505.00
- ACEA A3/B4
- MB –APPROVAL 229.3
- PORSCHE
- BMW

TECHNICAL DATA

CHARACTERISTICS	5W50 SN/CF FULL SYN
Specific gravity at 15 C	0.862
Kinematic viscosity at 40 C, mm ² /s (cSt)	130
Kinematic viscosity at 100 C, mm ² /s (cSt)	18.9
Viscosity index	165

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

