



SUPERTECH 15W40 CK-4

Code: 2004
Date: 10-01-2017

DESCRIPTION

HDDO 15W40 CK-4 is a Low SAPS, new generation, premium heavy duty diesel oil that has been formulated specifically to meet the latest Euro VI requirements of Australian and imported designed low emission engines. Designed and formulated to provide protection for highly rated diesel engines running in severe service conditions. It affords increased fuel economy and long drain intervals.

SUMMARY OF BENEFITS

- Supercedes CJ-4/SN
- Specially formulated to protect exhaust after DPF's
- Excellent soot dispersancy
- Superior friction and wear control

SPECIFICATIONS

- API CK-4/CJ-4/CI-4+/CI-4
- API SN
- MAN 3275 & 3575
- ACEA E9-12
- ACEA E7-12
- DQC III-10-LA
- CATERPILLAR ECF-3
- DETROIT DIESEL 93K222
- VOLVO VDS-4.5
- MB 228.31
- MTU 2.1
- CUMMINS 20086
- FORD WSS-M2C171-E
- FORD WSS-M2C171-F1
- MACK EO-O PREMIUM PLUS
- MACK EOS-4.5
- RENAULT VI RLD-4

TECHNICAL DATA

CHARACTERISTICS	HDDO 15W40 CK-4/SN
Specific gravity at 15 C	0.868
Kinematic viscosity at 40 C, mm ² /s (cSt)	102.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.0
Viscosity index	139

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043
Phone: 1300 46 33 33, Email: info@tritechlubricants.com
Web: www.tritechlubricants.com

