

AGRITRANS UTTO 10W30

Code: 4200 Date: 07-07-2017

DESCRIPTION

AGRITRANS UTTO is a multi-purpose Universal Tractor Transmission Oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti-squawk additive ensures effective operation of wet brakes.

AGRITRANS UTTO has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEM's. Tritech additive technology has been field tested in over 250 tractors and that combines to more than 200,000 hours of field tests.

SUMMARY OF BENEFITS

- Superior gear wear protection
- Correct frictional characteristics ensure quiet wet brake operation
- Proven field performance
- · Good anti-foam characteristics
- Excellent shear stability and thermal / oxidation stability provide long fluid life
- Good water tolerance ensures hydraulic performance is maintained
- Low copper activity
- Good filterability
- Excellent anti-squawk properties

SPECIFICATIONS

API GL-4 (80W)

ISO 68
ALLISON C4, C3
CATERPILLAR TO-2
KUBOTA UDT

• JI CASE JIC-143, 144, 145 (THC Fluid), 185 (TFD Fluid)

CASE (International)
MS-1204, 1205, 1206 (Powergard PFT), 1207 (Hy-Trans Plus), 1209, 1210

Int. Harvester Case
B5 & B-6 Hytran
CASE NEW HOLLAND
MAT3525, 3509, 3505

FORD NEW HOLLAND M2C134D, M2C86A/B/C, M2C77-A, M2C53-A, M2C48B/C, M2C41-B
MASSEY FERGUSON M-1110, 1127A&B, 1129A Permatran, 1135 Permatran III, 1141,1143 1145

• DEUTZ-ALLIS 25743 (PF-821XL), 257541, 246634 Hydr Trans Fluid

DEUTZ Hyrdra Trans Fluid

JOHN DEERE J14(A,B,C JDT303). J20(A,B Hy-Guard), J20C, J20D, J21A, J27 (10W or 30)

VCE WB 101

• WHITE Q1826, 1802 1766B (UTHF), 1766 1722 1705

ZF TE-ML06, ML-03

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: info@tritechlubricants.com

Web: www.tritechlubricants.com







AGRITRANS UTTO 10W30

Code: 4200 Date: 07-07-2017

TECHNICAL DATA

CHARACTERISTICS	AGRITRANS 10W30
Specific gravity at 15 C	0.8661
Kinematic viscosity at 40 C, mm2/s (cSt)	64
Kinematic viscosity at 100 C, mm2/s (cSt)	10.30
Viscosity index	149

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: info@tritechlubricants.com

Web: www.tritechlubricants.com



