



VACUUM PUMP OIL

ISO: 46, 55, 68, 100, 150

Code: 7068 to 7072

Date: 09-09-2019

DESCRIPTION

VACUUM PUMP OIL is a premium vacuum pump lubricant manufactured from selected group 2 base stocks specially designed for the dairy industry.

VACUUM PUMP OIL is blended to have low volatility and other unique characteristics make it especially suitable for use in most vacuum pumps.

SUMMARY OF BENEFITS

VACUUM PUMP OIL is an ideal choice of lubricant for all milking machines and industrial vacuum pumps. The oil has excellent demulsibility – readily separates from moisture that comes from water vapour which is inherent in many vacuum pump systems for easier removal of water that causes rusting and oil degradation.

TECHNICAL DATA

CHARACTERISTICS	ISO:46	ISO:55	ISO:68	ISO:100	ISO:150
Specific gravity at 15 C	0.865	0.871	0.873	0.876	0.890
Kinematic viscosity at 40 C, mm ² /s (cSt)	46	55	65	95	150
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.1	8.0	9.0	11.5	15.2
Viscosity index	113	114	115	100	102

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
 151 Colemans Road, Dandenong South VIC 3175
 Web: www.tritechlubricants.com
 Phone: 1300 46 33 33

