



COOLING SYSTEM FLUSH

Code: TQ015

DESCRIPTION

Cooling System Flush is a specially formulated liquid for removing sludge, grease and scale from radiators and engine water jackets. Cooling System Flush is non-acidic, solvent-less and biodegradable and is safe to use on both cast iron and aluminium alloy. It will not adversely affect water pump seals or radiator hoses.

FEATURES

- REMOVES rust, scale and sludge from radiators, engine blocks and heater cores, restoring cooling system efficiency for all seasons.
- NON-INJUROUS to rubber seals, O-rings and hoses.
- METAL components and water pumps are also unaffected.

APPLICATIONS

First drain the cooling system to ensure removal of coolant, additives and dispersed rust and scale that may be present.

Shake bottle well before use. Then half fill radiator with clean water, add 250 mls Cooling System Flush, and top up with water.

Run the engine for about 10 minutes, allow to cool, and then drain. Flush the system thoroughly with clean water, preferably by pressure flushing. For the removal of engine or transmission oil that has leaked into the cooling system, more than one application may be necessary.

The cooling system should then be refilled with clean water, preferably distilled water, and the appropriate amount of the TriTech Rust and Corrosion Inhibitor or Anti-freeze / Anti-boil Coolant.

Do not spill on paint work, and avoid contact with skin and eyes. Should contact occur or spillage occur flush immediately with clean water.

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: info@tritechlubricants.com

Web: www.tritechlubricants.com

