

## DESCRIPTION

**70W75 GL-4+ FULL SYNTHETIC** is a high viscosity index, full synthetic manual gearbox lubricant containing sophisticated extreme pressure additives and base oils. It is designed to give maximum protection to transaxles and gearboxes operating under the most arduous conditions. Designed for 5 and 6 speed manual gearboxes.

## SUMMARY OF BENEFITS

- Smooth shift
- Enhanced oxidation stability
- Assists in lower fuel consumption
- Full Synthetic for longer life
- Superior wear protection

## SPECIFICATIONS

- MTF BOT 338
- API GL-4+
- ZF TE-ML 11 (manual)
- TREMEC T-56

## TECHNICAL DATA

CHARACTERISTICS	GEAR OIL 70W75 GL-4+ FULL SYN
Specific Gravity @ 15°C	.859
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	38
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	7.5
Viscosity index	177

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

### TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043  
Phone: 1300 46 33 33, Email: [info@tritechlubricants.com](mailto:info@tritechlubricants.com)  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)

