



SYNTHETIC IGO

ISO: 150

Code: 9629

Date: 10-05-2017

DESCRIPTION

SYNTHETIC INDUSTRIAL GEAR OIL 150 is a premium quality, fully synthetic industrial lubricant made from a blend of Polyalphaolefin (PAO) synthetic base oils containing lead free extreme pressure agents. It has been developed to combine high load carrying capacity with high anti-friction characteristics. **SYN IGO 150** also has high corrosion protection and excellent water demulsibility.

SUMMARY OF BENEFITS

- Superior high & low temperature operation with natural high VI characteristics
- Excellent anti-oxidation resistance increasing lubricant life and less maintenance
- Excellent high film strength for superior wear protection and shock loads capability
- Outstanding flow properties yield lower power consumption and lower operating temperatures

SPECIFICATIONS

- API GL-3
- AGMA 250.04, 9005-D94
- US STEEL 224
- CINCINNATI MILACRON

TECHNICAL DATA

| CHARACTERISTICS | SYN IGO 150 |
|--|-------------|
| Specific gravity at 15 C | 0.850 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 150 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 19.5 |
| Viscosity index | 149 |

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

TRITECH LUBRICANTS AUSTRALASIA

116 Lambeck Drive, Tullamarine, VIC, 3043

Phone: 1300 46 33 33, Email: info@tritechlubricants.com

Web: www.tritechlubricants.com



AUSTRALIAN MADE AND
AUSTRALIAN OWNED