



# SYNTHETIC IGO

## ISO: 220

Code: 9630

Date: 10-05-2015

## DESCRIPTION

**SYNTHETIC INDUSTRIAL GEAR OIL 220** is a premium quality, fully synthetic industrial lubricant made from a blend of Polyalphaolefin (PAO) synthetic base oils containing lead free extreme pressure agents. It has been developed to combine high load carrying capacity with high anti-friction characteristics. **SYN IGO 220** also has high corrosion protection and excellent water demulsibility.

## SUMMARY OF BENEFITS

- Superior high & low temperature operation with natural high VI characteristics
- Excellent anti-oxidation resistance increasing lubricant life and less maintenance
- Excellent high film strength for superior wear protection and shock loads capability
- Outstanding flow properties yield lower power consumption and lower operating temperatures

## SPECIFICATIONS

- API GL-3
- AGMA 250.04, 9005-D94
- US STEEL 224
- CINCINNATI MILACRON

## TECHNICAL DATA

CHARACTERISTICS	SYN IGO 220
Specific gravity at 15 C	0.8510
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	215
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	25.0
Viscosity index	146.0

- Materials Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C
- Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

## TRITECH LUBRICANTS

15 Leah Grove, Carrum Downs, Victoria, Australia 3201

Phone: +61 3 9708 2317, Fax: +61 3 9708 2318

Email: [sales@tritechlubricants.com](mailto:sales@tritechlubricants.com),

Web: [www.tritechlubricants.com](http://www.tritechlubricants.com),



AUSTRALIAN MADE AND  
AUSTRALIAN OWNED