

DESCRIPTION

POLYTEC EHD EP2 is a multi-purpose premium quality long life grease that has been specifically designed for bearing lubrication under conditions of elevated temperature and high speeds. POLYTEC EHD EP2 is manufactured from a high viscosity index base oil which has been thickened with an advanced polyurea thickener.

POLYTEC EHD EP2 can be recommended for many general-purpose lubrications but it is especially recommended for high temperature / high-speed applications. Applications include anti-friction bearings in electric motors, turbines and generators. In industrial applications, its excellent water repellency makes it especially suitable for water pumps and other heavy duty applications in wet environments.

SUMMARY OF BENEFITS

- Outstanding Mechanical stability.
- Broad operating temperature range.
- Excellent water resistance
- Excellent protection against corrosion and wear.
- Very long-life product
- Good compatibility with other greases and lubricants
- Suitable for Sealed-for-Life Applications.

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	POLYUREA
TEXTURE	SLIGHTLY STRINGY
COLOUR	LIGHT GREEN
DROPPING POINT °C	250 MIN
FOUR BALL WELD LOAD, KGS	315
BASE OIL VISCOSITY @40°C	116 CST
OPERATING TEMPERATURE RANGE °C	-30 to 180

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C