



TURBOTECH 15W40 CF-4/SJ

Code: 2000

Date: 10-05-2015

DESCRIPTION

TURBOTECH 15W40 CF4/SJ is a versatile and economical high-performance diesel engine oil meeting API CF-4/SJ standards in diesel/ petrol lubrication. It has been specifically formulated as a stay in grade to equally perform in engines running on diesel, petrol or LPG, whether turbocharged, supercharged or naturally aspirated.

SUMMARY OF BENEFITS

- Recommended for turbocharged and non turbo charged diesel engines
- Recommended for European, Japanese and pre 1994 engines

SPECIFICATIONS

- API CF-4 / SJ
- MB 228.1
- MAN 271
- VOLVO VDS
- ACEA A2/B2, E2
- CATERPILLAR TO -2

TECHNICAL DATA

CHARACTERISTICS	TURBOTECH 15W40 CF-4/SJ
Specific gravity at 15 C	0.8710
Kinematic viscosity at 40 C, mm ² /s (cSt)	101
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.0
Viscosity index	140

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

