



# ULTRATECH 15W40 CH-4/SJ

Code: 2001

Date: 10-05-2015

## DESCRIPTION

**ULTRATECH 15W40 CH-4/SJ** is a mid-ash, heavy duty multigrade diesel engine oil designed for use in high speed, four stroke diesel engines meeting the requirements of American, European and Japanese engine manufacturers. ULTRATECH 15W40 CH-4/SJ has been formulated for heavy duty service in engines specifically designed for on- highway conditions as well as being suitable for a wide range of heavy-duty off-highway applications.

## SUMMARY OF BENEFITS

- Sludge and soot control
- Superior friction and wear control

## SPECIFICATIONS

- CUMMINS CES 20076, 20072, 20071
- API CH-4, CG-4/ CF-4, / SJ
- MTU / DDC TYPE 2
- MACK EO-M+
- JASO DH-1
- ACEA E5/ E3
- VOLVO VDS-3
- CAT ECF-1
- MB 228.3

## TECHNICAL DATA

CHARACTERISTICS	ULTRATECH 15W40 CH-4/SJ
Specific gravity at 15 C	0.875
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	101
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14.0
Viscosity index	140

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

**TRITECH LUBRICANTS AND SALES PTY LTD**  
151 Colemans Road, Dandenong South VIC 3175  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)  
Phone: 1300 46 33 33

