



GEAR LUBE LS90 GL5

Code: 4006

Date: 15-08-2015

DESCRIPTION

GEAR LUBE LS 90 GL5 is an extreme pressure, heavy duty, high performance gear lubricant recommended for spiral or hypoid axles, both with and without "limited slip" design. It contains extreme pressure additives and special friction modifiers to reduce and prevent squeal in limited slip differentials.

SUMMARY OF BENEFITS

- Protects from heavy loads and shock loading
- Advanced friction modifiers to reduce squeal
- Provides smooth power take up
- Superior wear protection

SPECIFICATIONS

- MILITARY SPECIFICATIONS MIL-PRF-2105E
- ZF TE-ML 07A, ZF TE-ML 08
- FORD- M2C118-A
- DAIMLER MS5630
- DANA 40819
- ISO 12925-1 CKC/CKD
- DIN 51517 PART 3
- AGMA 9005-E02
- API GL5
- USS 224

TECHNICAL DATA

CHARACTERISTICS	GEAR LUBE LS90 GL5
Specific gravity at 15 C	0.890
Kinematic viscosity at 40 C, mm ² /s (cSt)	170
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.0
Viscosity index	110

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

