



INDUSTRIAL GEAR OIL

ISO: 460

Code: 7025

Date: 10-04-2020

DESCRIPTION

IGO 460 is a premium quality, heavy duty industrial gear lubricant manufactured from highly refined base stocks and extreme pressure additives. Designed for use in all types of industrial gear boxes and can also be used in sprockets, chain drives and slide guides.

SUMMARY OF BENEFITS

- Wear protection even on occasional metal to metal contact
- Protects against rust and corrosion
- Provides excellent micro-pitting protection
- Good oxidation and thermal stability for long life
- Excellent demulsibility for easy water separation

SPECIFICATIONS

- DAVID BROWN TYPES M, A, E
- AGMA 9005-E02
- DIN 51517 (PART 3)
- ISO 12925-1 CKD
- US STEEL 224

TECHNICAL DATA

CHARACTERISTICS	IGO 460
Specific gravity at 15 C	0.900
Kinematic viscosity at 40 C, mm ² /s (cSt)	440
Kinematic viscosity at 100 C, mm ² /s (cSt)	30.6
Viscosity index	97.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

