



SYNERGY EURO

5W30 E6

LOW SAPS

Code: 9243

Date: 14-12-2019

DESCRIPTION

SYNERGY EURO 5W30 E6 is a full synthetic, energy-conserving, ultra-high performance, heavy duty diesel engine oil. It meets and complies with the demanding requirements of Euro 6 exhaust emission legislation. SYNERGY EURO 5W30 E6 is also backwards compatible to European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3, Euro 4 and Euro 5 exhaust emission legislation.

SUMMARY OF BENEFITS

- Low viscosity, full synthetic formulation
- Suitable for use where particulate filters are used
- Outstanding low temperature viscosity characteristics for reduced wear at start up
- Low SAPS (Sulfated Ash, Phosphorous and Sulfur)
- Super extended drain intervals surpassing any mineral or American diesel type lubricant
- Reduced fuel consumption with lower viscosity
- Excellent soot and sludge control resulting in cleaner engines
- High oil film strength even at extreme loads

SPECIFICATIONS

- API CK-4, CJ-4, CI-4
- MAN 3275 /3575 / 3677 / 3271-1
- MB 228.51
- ACEA E6 / E7 / E9
- ACEA E4 (suitable for use)
- RENAULT TRUCK RLD-3 / 4
- MTU TYPE 2.1, II
- SCANIA LOW ASH, LDF / LDF-2
- MACK EO-S4.5, EO-O P PLUS 7
- VOLVO VDS 3, 4, 4.5
- CUMMINS CES 20081 / 20086
- DEUTZ DQC IV-10 LA / DQC III-10 LA
- DAF
- JASO DH-1, DH-2, GLOBAL DHD-1
- CATERPILLAR ECF-3, ECF-2, ECF-1A
- DD DFS 93K222, 93K218, 7SE-270, 2000/4000 CAT-1

TECHNICAL DATA

CHARACTERISTICS	5W30 E6 LOW SAPS
Specific gravity at 15 C	0.850
Kinematic viscosity at 40 C, mm ² /s (cSt)	69
Kinematic viscosity at 100 C, mm ² /s (cSt)	11.5
Viscosity index	162

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
 151 Colemans Road, Dandenong South VIC 3175
 Web: www.tritechlubricants.com
 Phone: 1300 46 33 33

