



# SYNERGY EURO 5W40 C3

Code: 9282

Date: 10-10-2020

## DESCRIPTION

**SYNERGY EURO 5W40 C3** is designed for European engines requiring SHPD (Super High-Performance Diesel) level of performance and those which comply with the latest European exhaust emission legislation. SYNERGY EURO 5W40 C3 is a full synthetic mid SAPS formulation and is suitable for use where particulate filters are used.

## SUMMARY OF BENEFITS

SYNERGY EURO 5W40 C3 provides excellent wear protection at start up and during high speeds and/or high loads. SYNERGY EURO 5W40 C3 has excellent oxidation resistance and outstanding sludge control resulting in cleaner engines and longer drain intervals. Its low/mid SAPS formulation makes it suitable for use where DPFs are in use.

## SPECIFICATIONS

- ACEA C3, C2 (SFU)
- VW 502.00, 505.00, 505.01
- API SN/CF
- MB 229.31/ 229.51/ 226.5
- RENAULT RN0700 / 0710
- BMW LONGLIFE- 04
- GM DEXOS 2
- PORSCHE A40
- FORD WSS-M2C917-A
- DAIMLER CHRYSLER MS 6395K

## TECHNICAL DATA

CHARACTERISTICS	5W40 C3 LOW SAPS
Specific gravity at 15 C	0.868
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	92
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14.8
Viscosity index	169

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

**TRITECH LUBRICANTS AND SALES PTY LTD**  
151 Colemans Road, Dandenong South VIC 3175  
Web: [www.tritechlubricants.com](http://www.tritechlubricants.com)  
Phone: 1300 46 33 33

